



AH-64  
Apache Helicopter  
R&D Team

## PENETRATING LUBRICANT

**Only non-flammable Nano penetrating oil on the market.**

- Protects against corrosion and rust at the Nano level.
- Prolongs equipment life far better than traditional lubricants.
- Reduces friction to extraordinarily low levels to reduce wear and improve efficiency.
- Penetrates deeply to break friction welds.
- Lubricates to reduce maintenance time and extends repair cycles.
- Resistant to moisture and chemicals.
- Cuts through grease.
- Quickly penetrates corrosion.
- Foaming action for 100% coverage.
- Excellent penetration and creep properties.

Works great on locks, rusted nuts, bolts, and sliding mechanisms.

Perfect for use on Aviation, Auto, Industrial, Marine and Other Mechanical Equipment.



# NANO **Pro MT** <sup>TM</sup>

Conor Daly  
Nano Racing Team  
Indycar Series

# 18

ncorcenter.com



**NANO ProMT Penetrating Lubricant** is an innovative formula with universal capabilities. Developed to lubricate deeply into the spaces between rusted, metal-to-metal parts. It speeds maintenance activities and provides a barrier to future corrosion and rust. Foaming action and excellent creep properties allow the nano particles to achieve 100% coverage for fast removal of friction welded components.

| DESCRIPTION            | NANO PENETRATING LUBRICANT          |
|------------------------|-------------------------------------|
| PART#                  | NDT11P                              |
| UPC CODE               | 8 53770 00408 8                     |
| SCC CODE               | 1 08 53770 00408 5                  |
| HARMONIC CODE          | 2710.19.30                          |
| PACKAGE CONTENTS       | 11 oz                               |
| SELLING UNIT WEIGHT    | 0.85 pounds                         |
| SELLING UNIT DIMENSION | 2.6" x 2.6" x 7.9"                  |
| SELLING UNIT CUBE      | 0.030 cubic feet                    |
| CASE PACK              | 12                                  |
| CASE WEIGHT            | 12 pounds                           |
| CASE DIMENSION         | 10.9" x 8.4" x 8.8"                 |
| CASE CUBE              | 0.46 cubic feet                     |
| CASES PER PALLET       | 108                                 |
| CASES/LAYER            | 18                                  |
| LAYERS/PALLET          | 6                                   |
| WEIGHT/PALLET          | 1,134 + 40 (total weight 1,174 lbs) |



NANO ProMT • 7427 Matthews Mint Hill Rd • Ste 201  
Mint Hill • NC 28227 • [www.nanoprompt.com](http://www.nanoprompt.com) • Made in USA





AH-64  
Apache Helicopter  
R&D Team



## DRY LUBRICANT

- Prolongs equipment life far better than traditional lubricants.
- No oily residue. Nonstick.
- Moisture-displacing film leaves white powder.
- Dries fast to prevent the collection of dirt and dust.
- Ozone friendly - CFC and Tricholethane free.
- Perfect for polymers and ceramics.
- Protects against corrosion and rust at the Nano level.
- Reduces friction to extraordinarily low levels to reduce wear and improve efficiency.
- Penetrates deeply to break friction welds.
- Lubricates to reduce maintenance time and extends repair cycles.

Works great on Garage Doors, RV Slide-outs, Hinges, Gears, Chains, Ignition, Motors, Firearms, Reciprocating Sliding Mechanisms and Window Tracks.

Perfect for use on Aviation, Auto, Industrial, Marine and Other Mechanical Equipment.

# NANO **Pro MT** <sup>TM</sup>

Conor Daly  
Nano Racing Team  
Indycar Series

# 18

ncercenter.com



**NANO ProMT Dry Lubricant** is a highly engineered mixture of Dry Lube with CERFLON and NANO materials suspended in lubricating oil. It stays put, without squeezing out like liquid lubricants, making NDT11D ideal for reciprocating motions applications such as gear and chain lubrication. Superior nano materials lubricate to reduce friction and wear, preventing fretting and galling even in extreme pressure and high temperature applications. The CFC and 1,1,1-Trichloroethane free aerosol dries fast and clean, with no oily residue, providing instant, long lasting protection.

| DESCRIPTION            | DRY LUBRICANT                        |
|------------------------|--------------------------------------|
| PART#                  | NDT11D                               |
| UPC CODE               | 8 53770 00407 1                      |
| SCC CODE               | 1 08 53770 00407 8                   |
| HARMONIC CODE          | 2710.19.30                           |
| PACKAGE CONTENTS       | 11 oz                                |
| SELLING UNIT WEIGHT    | 0.96 pounds                          |
| SELLING UNIT DIMENSION | 2.6" x 2.6" x 7.9"                   |
| SELLING UNIT CUBE      | .030 cubic feet                      |
| CASE PACK              | 12                                   |
| CASE WEIGHT            | 12 pounds                            |
| CASE DIMENSION         | 10.9" x 8.4" x 8.8"                  |
| CASE CUBE              | 0.46 cubic feet                      |
| CASES PER PALLET       | 108                                  |
| CASES/LAYER            | 18                                   |
| LAYERS/PALLET          | 6                                    |
| WEIGHT/PALLET          | 1,296 / 40 (total weight 1,336 lbs.) |



NANO ProMT • 7427 Matthews Mint Hill Rd • Ste 201  
Mint Hill • NC 28227 • [www.nanoprompt.com](http://www.nanoprompt.com) • Made in USA





AH-64  
Apache Helicopter  
R&D Team



## DRY LUBRICANT

- Prolongs equipment life far better than traditional lubricants.
- No oily residue. Nonstick.
- Moisture-displacing film leaves white powder.
- Dries fast to prevent the collection of dirt and dust.
- Ozone friendly - CFC and Tricholethane free.
- Perfect for polymers and ceramics.
- Protects against corrosion and rust at the Nano level.
- Reduces friction to extraordinarily low levels to reduce wear and improve efficiency.
- Penetrates deeply to break friction welds.
- Lubricates to reduce maintenance time and extends repair cycles.

Works great on Garage Doors, RV Slide-outs, Hinges, Gears, Chains, Ignition, Motors, Firearms, Reciprocating Sliding Mechanisms and Window Tracks.

Perfect for use on Aviation, Auto, Industrial, Marine and Other Mechanical Equipment.

# NANO **Pro MT**™

Conor Daly  
Nano Racing Team  
Indycar Series

# 18

ncorcenter.com



**NANO ProMT Dry Lubricant** is a highly engineered mixture of Dry Lube with CERFLON and NANO materials suspended in lubricating oil. It stays put, without squeezing out like liquid lubricants, making NDT11D ideal for reciprocating motions applications such as gear and chain lubrication. Superior nano materials lubricate to reduce friction and wear, preventing fretting and galling even in extreme pressure and high temperature applications. The CFC and 1,1,1-Trichloroethane free aerosol dries fast and clean, with no oily residue, providing instant, long lasting protection.

| DESCRIPTION            | DRY LUBRICANT (CA ONLY)              |
|------------------------|--------------------------------------|
| PART#                  | NDT11DCA                             |
| UPC CODE               | 8 53770 00430 9                      |
| SCC CODE               | 1 08 53770 00430 6                   |
| HARMONIC CODE          | 2710.19.30                           |
| PACKAGE CONTENTS       | 11 oz                                |
| SELLING UNIT WEIGHT    | 0.96 pounds                          |
| SELLING UNIT DIMENSION | 2.6" x 2.6" x 7.9"                   |
| SELLING UNIT CUBE      | .030 cubic feet                      |
| CASE PACK              | 12                                   |
| CASE WEIGHT            | 12 pounds                            |
| CASE DIMENSION         | 10.9" x 8.4" x 8.8"                  |
| CASE CUBE              | 0.46 cubic feet                      |
| CASES PER PALLET       | 108                                  |
| CASES/LAYER            | 18                                   |
| LAYERS/PALLET          | 6                                    |
| WEIGHT/PALLET          | 1,296 / 40 (total weight 1,336 lbs.) |



NANO ProMT • 7427 Matthews Mint Hill Rd • Ste 201  
Mint Hill • NC 28227 • [www.nanoprompt.com](http://www.nanoprompt.com) • Made in USA



AH-64  
Apache Helicopter  
R&D Team



## OIL STABILIZER

- Extends oil life up to 100%.
- Improves horsepower.
- Protects against friction and engine wear.
- Protects against viscosity breakdown.
- Improves oil pressure and reduces temperature.
- Reduces dry starts.
- Reduces knocking.
- Compatible with synthetics.
- Up to 40% reduction in scarring in the 4-Ball Wear Test.
- Up to 68% reduction in wear metals.
- Up to 60% faster in reducing oil temperatures.
- Anti-foaming qualities to increase performance.

Works great and field-tested on Race Cars, Conventional Cars, SUV's & Trucks, Marine Engines, RV, Industrial Motors, Class 1-8 Trucks and Buses.

# NANO **Pro MT** <sup>TM</sup>

Conor Daly  
Nano Racing Team  
Indycar Series

# 18







**MADE IN**  
  
**THE USA**

**NANO ProMT Oil Stabilizer** is a Military Tough/Race Ready, extreme pressure Oil Stabilizer engineered to protect vital engine components against friction and engine wear. Using NANO ProMT Oil Stabilizer reduces oil temperatures up to 60% faster than standard lubricants, it reduces dry starts and viscosity breakdown for improved horsepower and oil pressure. All of which extends oil life up to 100%.

| DESCRIPTION            | SYNTHETIC OIL STABILIZER             |
|------------------------|--------------------------------------|
| PART#                  | NDT32OS                              |
| UPC CODE               | 853770004149                         |
| SCC CODE               | 10853770004146                       |
| HARMONIC CODE          | 3811.21.00                           |
| PACKAGE CONTENTS       | 32 oz                                |
| SELLING UNIT WEIGHT    | 2.0833 pounds                        |
| SELLING UNIT DIMENSION | 3.43" x 3.43" x 11.75"               |
| SELLING UNIT CUBE      | .077 cubic feet                      |
| CASE PACK              | 12                                   |
| CASE WEIGHT            | 25 pounds                            |
| CASE DIMENSION         | 14" x 10.75" x 12.5"                 |
| CASE CUBE              | 1.09 cubic feet                      |
| CASES PER PALLET       | 11                                   |
| CASES/LAYER            | 4                                    |
| LAYERS/PALLET          | 44                                   |
| WEIGHT/PALLET          | 1,150 + 40 (total weight 1,190 lbs.) |



NANO ProMT • 7427 Matthews Mint Hill Rd • Ste 201  
 Mint Hill • NC 28227 • [www.nanopromt.com](http://www.nanopromt.com) • Made in USA





AH-64  
Apache Helicopter  
R&D Team



## 75W90 SYNTHETIC GEAR OIL

- Increases thermal conductivity by up to 11%.
- Increases viscosity by up to 12%.
- Protects against viscosity breakdown.
- Up to 40% reduction in scarring in the 4-Ball Wear Test.
- Extends gear oil life up to 100%.
- Up to 16% increase in load capacity to failure.
- Up to 60% faster in reducing gear oil temps.
- Up to 25% reduction in gearbox temperature.
- Anti-foaming qualities to increase performance.
- Compatible with synthetics.

Works great and has been field-tested on Race Cars, Conventional Cars, SUV's, Trucks, RV, Marine Outdrives, Industrial Gear sets, Liquid Bath Wheel Hubs, Class 1-8 Trucks and Buses.

# NANO **Pro MT**

Conor Daly  
Nano Racing Team  
Indycar Series

# 18





**NANO ProMT Synthetic Gear Oil** is a Military Tough/Race Ready, extreme pressure gear lubricant engineered with synthetic base stocks and “NANO” technology additives which provide superior performance compared to leading brands. NANO Gear Oils are formulated to provide extreme pressure protection, extreme load carrying capacity, high performance corrosion protection, and superior thermal stability. All with an anti-foaming quality to increase performance.

| DESCRIPTION            | SYNTHETIC GEAR OIL 75W 90            |
|------------------------|--------------------------------------|
| PART#                  | NDT32GO                              |
| UPC CODE               | 853770004163                         |
| SCC CODE               | 10853770004160                       |
| HARMONIC CODE          | 3811.21.00                           |
| PACKAGE CONTENTS       | 32 oz                                |
| SELLING UNIT WEIGHT    | 2.0833 pounds                        |
| SELLING UNIT DIMENSION | 3.43” x 3.43” x 11.75”               |
| SELLING UNIT CUBE      | .077 cubic feet                      |
| CASE PACK              | 12                                   |
| CASE WEIGHT            | 25 pounds                            |
| CASE DIMENSION         | 14” x 10.75” x 12.5”                 |
| CASE CUBE              | 1.09 cubic feet                      |
| CASES PER PALLET       | 11                                   |
| CASES/LAYER            | 4                                    |
| LAYERS/PALLET          | 44                                   |
| WEIGHT/PALLET          | 1,150 + 40 (total weight 1,190 lbs.) |



NANO ProMT • 7427 Matthews Mint Hill Rd • Ste 201  
Mint Hill • NC 28227 • [www.nanoprompt.com](http://www.nanoprompt.com) • Made in USA





AH-64  
Apache Helicopter  
R&D Team



## High-Temp Extreme Pressure Grease

- Reduces wear and increases equipment efficiencies
- Outstanding high-temperature and low temperature performance.
- Superb thermal stability and oxidation resistance.
- Excellent protection against wear, rust and corrosion.
- Excellent pumpability.
- Outstanding structural stability in the presence of water.
- Low coefficient of friction.
- Stabilizes grease temperature and increases thermal conductivity.
- Reduces equipment wear.
- Extends lubrication intervals.

Works great and has been field-tested on Race Cars, Conventional Cars, SUV's, Trucks, RV, Industrial Bearings, Class 1-8 Trucks and Buses. Perfect for high-speed and low-speed bearings and main bearings under heavy loads.

# NANO **Pro MT**

Conor Daly  
Nano Racing Team  
Indycar Series

# 18

ncorcenter.com



**NANO ProMT High-Temp Extreme Pressure Grease** is formulated with special Nano Technologies to provide excellent protection against wear, rust and corrosion at high and low temperatures. It contains unique, synthetic base fluids combined with high quality lithium complex thickener and is free of wax to create a low coefficient of friction while providing low temperature pumpability and very low starting and running torque.

| DESCRIPTION                    | HIGH-TEMP EXTREME PRESSURE GREASE        |
|--------------------------------|------------------------------------------|
| PART#                          | NDT14GR                                  |
| UPC CODE                       | 853770004064                             |
| SCC CODE                       | 10853770004061                           |
| HARMONIC CODE                  | 2710.19.4000                             |
| PACKAGE CONTENTS               | 14 oz                                    |
| SELLING UNIT WEIGHT LBS        | 0.95                                     |
| SELLING UNIT DIMENSION O.D.    | 2.13" x 2.13" x 9.31"                    |
| SELLING UNIT CUBE FOOT         | 0.024                                    |
| CASE PACK                      | 10                                       |
| CASE WEIGHT LBS                | 10.05                                    |
| CASE DIMENSION O.D.            | 10.88" x 4.44" x 9.5"                    |
| CASE CUBE FOOT                 | 0.27                                     |
| CASES PER PALLET               | 120                                      |
| CASES/LAYER                    | 30                                       |
| LAYERS/PALLET                  | 4                                        |
| WEIGHT/PALLET LBS +40LB PALLET | 1,557.5 + 40 (total weight 1,597.5 lbs.) |



NANO ProMT • 7427 Matthews Mint Hill Rd • Ste 201  
Mint Hill • NC 28227 • [www.nanopromt.com](http://www.nanopromt.com) • Made in USA





AH-64  
Apache Helicopter  
R&D Team



## Marine Grease

- Superior friction, rust & corrosion protection.
- Designed for light and heavy duty trailer wheel bearings.
- Excellent thermal stability and oxidation resistance.
- Corrosion protection from road salt and harsh marine environments.
- Extends maintenance cycles.
- Highly adhesive and cohesive structure.
- Resistance to thermal, oxidative and structural degradation at high temperature applications.
- Protection of lubricated parts even in hostile aqueous environments.
- Enhance bearing protection in high temperature applications.
- Operating range of -40°F to +500°F (-40°C to +260°C)

Works great for pumps, winches, Class 1-8 trailer fifth wheels, wheel bearings, and landing gear. Perfect for Marine use outboards and lower units.

# NANO **Pro MT** <sup>TM</sup>

Conor Daly  
Nano Racing Team  
Indycar Series

# 18

ncorcenter.com



**NANO ProMT Marine Grease** is specifically designed with special Nano Technologies to provide excellent protection against wear, rust and corrosion at extreme temperatures. Our Marine Grease contains unique, synthetic base fluids combined with high quality lithium complex thickener and it's free of wax. This creates a low coefficient of friction that provides excellent low temperature pumpability and very low starting and running torque.

| DESCRIPTION                    | MARINE GREASE                            |
|--------------------------------|------------------------------------------|
| PART#                          | NDT14MG                                  |
| UPC CODE                       | 853770004101                             |
| SCC CODE                       | 10853770004108                           |
| HARMONIC CODE                  | 2710.19.4000                             |
| PACKAGE CONTENTS               | 14 oz                                    |
| SELLING UNIT WEIGHT LBS        | 0.95                                     |
| SELLING UNIT DIMENSION O.D.    | 2.13" x 2.13" x 9.31"                    |
| SELLING UNIT CUBE LBS          | 0.024                                    |
| CASE PACK                      | 10                                       |
| CASE WEIGHT LBS                | 10.05                                    |
| CASE DIMENSION O.D.            | 10.88" x 4.44" x 9.5"                    |
| CASE CUBE FOOT                 | 0.27                                     |
| CASES PER PALLET               | 150                                      |
| CASES/LAYER                    | 30                                       |
| LAYERS/PALLET                  | 5                                        |
| WEIGHT/PALLET LBS +40LB PALLET | 1,557.5 + 40 (total weight 1,597.5 lbs.) |



NANO ProMT • 7427 Matthews Mint Hill Rd • Ste 201  
Mint Hill • NC 28227 • [www.nanoprompt.com](http://www.nanoprompt.com) • Made in USA





AH-64  
Apache Helicopter  
R&D Team

## High-Performance Heat Transfer Coolant

- Reduces or eliminates bubbles or vapor barrier (cavitation) that form on hot metal surfaces to reduce coolant temperatures by up to 12°F (-11°C).
- Increases horsepower.
- Extends engine life.
- Superior heat transfer properties compared to glycol-based antifreeze.
- Compatible with new or used antifreeze to improve the heat transfer of ethylene and propylene glycol systems.
- Improves heat transfer and reduces cylinder head temperature.
- Reduces engine oil temperature.
- Nano Cool contains lubricity enhancers for improved water pump reliability.
- Increase thermal uptake and viscosity for better flow and heat transfer.

Perfect for use in high revving street, off-road, motorcycles, ATV, Marine engines. Engineered for today's cast iron, copper, aluminum, brass and bronze cooling systems.

Proven in open wheel and stock car racing.



# NANO <sup>Pro MT</sup>

Conor Daly  
Nano Racing Team  
Indycar Series

# 18





**NANO ProMT High-Performance Coolant** is the First Product of its kind to utilize today's enhanced nano-sized materials suspended in de-ionized water to displace heat faster and more efficiently than any other coolant. Engines run cooler and more reliably with less catastrophic failures. It also addresses problems related to excessive heat buildup, such as seal and oil damage, leaking, and abnormal wear.

| DESCRIPTION                    | HIGH-PERFORMANCE HEAT TRANSFER COOLANT |
|--------------------------------|----------------------------------------|
| PART#                          | NDT16NC                                |
| UPC CODE                       | 8 53770 00427 9                        |
| SCC CODE                       | 1 08 53770 00427 6                     |
| HARMONIC CODE                  | TBD                                    |
| PACKAGE CONTENTS               | 16 OZ                                  |
| SELLING UNIT WEIGHT LBS        | 2.0833                                 |
| SELLING UNIT DIMENSION O.D.    | 2.60" x 2.60" x 9.30"                  |
| SELLING UNIT CUBE FOOT         | .044                                   |
| CASE PACK                      | 12                                     |
| CASE WEIGHT LBS                | 12                                     |
| CASE DIMENSION O.D.            | 11" x 8.4" x 10"                       |
| CASE CUBE                      | 0.53 cubic feet                        |
| CASES PER PALLET               | 1296                                   |
| CASES/LAYER                    | 72                                     |
| LAYERS/PALLET                  | 18                                     |
| WEIGHT/PALLET LBS +50LB PALLET | 1,296 + 40 (total weight 1,336 lbs.)   |



NANO ProMT • 7427 Matthews Mint Hill Rd • Ste 201  
Mint Hill • NC 28227 • [www.nanopromt.com](http://www.nanopromt.com) • Made in USA